

Toll-Free
1-800-268-6166

CRI Digital Solutions Inc.

4324 N. Hight St.

Columbus, OH 43214

9002/10512 Specifications

Copier Specifications

| | |
|--------------------------------|---|
| Printing Process | 4 Way Laser Diode Array, Dry Process (Dual Component) |
| Reading Element | 4 Channel CCD Array |
| Configuration | Console |
| Copy/Print Resolution | 1200 x 1200 dpi |
| Scanning Resolution | 600 dpi |
| Gray Scale | 256 Levels |
| Standard Memory | 128 MB (RAM); 40 GB x 2 (HDD) |
| Document Server | Storage up to 15,000 Pages |
| <u>Speed</u> | |
| First Copy | 3.5/3.2 Seconds (platen) |
| Continuous Copy Speed | 90/105 Copies/Minute |
| Multiple Copy | Up to 9,999 |
| <u>Original /Copy Size</u> | |
| Original Type | Book/Sheet |
| Original Size | Up to 11" x 17" |
| Copy Size | 5.5" x 8.5" - 11" x 17" |
| Copy Type | Plain Paper, Transparencies, Tabs, Index, Covers |
| <u>Duplex</u> | |
| Type | Four Pages Stackless Interleave |
| Capacity | Unlimited |
| Paper Size | 5.5" x 8.5" - 11" x 17" |
| Paper Weight | 20 lb. Bond - 90 lb. Index |
| Reduction/Enlargement | 25%, 50%, 65%, 73%, 78%, 85%, 93%, 121%, 129%, 155%, 200%, 400% plus two user programmable ratios |
| Zoom | 25% - 400% in 1% increments |
| User Codes | 500 eight digits copier; 500 eight digits printer |
| Warm Up Time | Less than 360 Seconds, 500 copier (8 digits) |
| Quantity Indicator | 1 to 9,999 |
| Power Source | 240V/60 Hz/20 A |
| Dimensions (W x D x H) | 82.8" x 33.8" x 58.1" (Main Frame) 91.3" x 33.8" x 58.1" (Full System) |
| Weight | 859.4 lbs. |
| <u>Paper Supply (Standard)</u> | |
| Paper Feed | 1,000 Sheets x 2 Trays (Tandem Tray) 500 Sheets x 2 Trays |
| Paper Size | 5.5" x 8.5" - 11" x 17" (12" x 18" with Optional Bypass Tray) |
| Paper Weight | 16 lb. Bond to 90 lb. Index (depending on Tray) |
| Total Capacity | 8,050 Sheets (with Optional LCT and Bypass Tray) |

Document Server Specifications

| | |
|------------------|-------------------------------------|
| Number of Jobs | Up to 3,000 |
| Number of Pages | Up to 2,000 per document |
| Maximum Capacity | 15,000 Pages |
| User ID | Max 8 Letters (Alphanumeric) |
| File Name | Max 8 Letters (Alphanumeric Option) |
| Password | Max 4 digits (Numeric Option) |

| | |
|-----------------------------|---|
| Support OS | Windows 95/98, Win ME, Win NT 4.0, Windows 2000, Win XP, Macintosh, UNIX |
| Supported Printer Languages | PCL 5e, PCL6, RPCS; Postscript 3 (Option) |
| Document Server Features | Booklet and Magazine Mode, Printing, Sample Sets, Change File Name, Save Printing Conditions, Connect Copy |
| Document Editor Functions | Print, Set Password, Job Preset (10 Jobs), Merge File, Sort By User ID or Time, Search by Document File Name) Change File Name, Delete File, File Insertion, Delete Page, Insert Page, File Merge |

Standard Accessories

Auto Reversing Document Feeder

| | |
|-------------------------|---|
| Original Feeding Speed | 80 OPM |
| Original Size | 5.5" x 8.5" to 11" x 17" |
| Original Weight | 16-42 lb. Bond (Simplex) 16-34 lb. Bond (Duplex) |
| Original Stack Capacity | 100 Sheets |
| Original Set | Face Up |