

## 1302/1302f Specifications

Configuration	Digital Copier
Copying Process	Dry electrostatic transfer
Recording Method	Laser
Toner	Dual Component
Copier Memory	8 MB expandable to 40 MB
Resolution	600 dpi
Gray Scale	256 levels
Continuous Copy Speed	13cpm - letter size
Multiple Copy	Up to 99
Warm-Up Time	20 seconds
First-Copy Time	8 seconds
Original Size	Up to 11" x 17" (platen) Up to 8.5" x 14" (requires ADF)
Output Document Size	5.5" x 8.5" - 8.5" x 14"
Standard Paper Supply	1 x 250 sheet drawers, 100 sheet bypass
Maximum Paper Capacity	850 sheets
Paper Output Capacity	250 sheets internal tray
Paper Weight	Drawers: 16-24 lbs.; Bypass: 16-42 lbs.
Zoom Range	50%-200% in 1% increments
Reduction Ratios	93%, 78%, 65%
Enlargement Ratios	129%, 155%
Dimensions	18.4"W x 17.7"D x 14.6"H (1302) 18.4"W x 17.7"D x 18.4"H (1302f)
Power Source	120V/60Hz 15A
Weight	44 lbs (1302); 48 lbs. (1302f).
Other Features	Auto Image Density, Auto Off, Auto Start, Auto Reduce/Enlarge, Energy Save Mode, Photo Mode, Combine Originals 2, User Codes (10), Scan Once/ Print Many, Optional Electronic Sort, Optional Auto Tray Switch.

## Printer Module Option

Print Speed	13 ppm
CPU	75 MHz
Memory Capacity	16 MB standard, expandable to 144 MB Memory
Printer Languages	PCL6/5e (standard); PS2 emulation (option)
Interface	Parallel IEEE1284, NIB (option)
Driver	Windows 95/ 98/ NT 4.0/ 200/ Me, Macintosh 8.x/ 9.x
Fonts	35 Intellifonts, 10 TrueType, 80 PostScript (option)
Resolution	600 dpi
Topologies	Ethernet (10/100 Base T)
Network Protocols	TCP/IP, IPX/SPX, NetBEUI, AppleTalk (Auto Switching)
Network Operating	Novell NetWare 3.x, 4.x, 5.0 and Systems Intranetware; Microsoft Windows 95/98/NT4.0/2000; Mac OS 8.x, 9.x
Other Features	Collation, Slip Sheet, Edge Smoothing, WaterMarks, SmartNetMonitor, Tray Locking, Document Printing

## 2513f Fax Module

Print Speed	13 ppm
Compatibility	Group 3, ITU. T
Modem Speed	33.6 Kbps with automatic shutdown
Transmission Speed	3 seconds
Scanning speed	2.4 seconds (8.5" x 11")
Compression Method	MH, MR, MMR
Standard Memory	5 MB (shared with copier memory)
Transmission/Reception	Up to 8.5" x 14"
Auto Dial	16 quick, 50 speed, 5 groups
Other Features	Send Later, Direct fax Number Entry, Dual Access, Label Insertion, Restriction Reduction, Send Later, Direct Fax, Number Entry, Label Insertion, Restricted Access, Telephone Directory, Batch Transmission, Forwarding, Twelve Hour Memory Backup, Reception Time Printing,

